

Self-Storage Development

Stormwater Management Report

Project Location:

Road 120
St. Marys, Ontario

Prepared For:

C&C Stonetown Management

Prepared by:

GRIT Engineering Inc.
169 Huron Street, Ontario

December 20, 2021

Revision 1

GRIT File No: GE021-21



Contents

1.0	Introduction	3
2.0	Design Requirements for Approval	5
3.0	Stormwater Management Design	6
3.1	Design Approach	6
3.2	Predevelopment Condition	6
3.3	Post Development Condition	7
3.4	Quantity Control Summary	7
3.5	Quality Control Summary	7
3.6	Erosion & Sedimentation Control.....	8
4.0	Design Summary	12
5.0	Design Recommendations	13

Appendices

Appendix A – Stormwater Quantity Control Calculations

Appendix B – Design Drawings



1.0 Introduction

GRIT Engineering Inc. (GRIT) was retained by C&C Stonetown Management to design the private stormwater management system for the proposed self-storage development to satisfy the site plan approval requirements set forth by the Town of St. Marys.

The proposed development is located on the south side of Highway 9 and west of Road 120 in St. Marys, Ontario and is approximately 2.04 hectares in size. The site is bounded by existing Highway Commercial (zone C3-7) to the west, existing agricultural (zone A) to the east, existing agricultural (zone A-16) to the south and existing Highway Commercial (zone C3) to the north. Figure 1 provides a 2018 aerial image, illustrating the site location and surrounding characteristics.

The Stormwater Management (SWM) report will provide the necessary background and proposed design information to address the site plan approval requirements for the subject site. Furthermore, this SWM report is to be read in conjunction with the included GRIT engineering design drawings, which provides details the proposed design and construction details.



IMAGE SOURCE: MICROSOFT BING MAPS



169 HURON STREET
STRATFORD, ON
N5A 5S9
www.gritengineering.ca

Legend

Project:
ROAD 120
SELF STORAGE UNITS

Figure Title:
SITE LOCATION
ST. MARYS, ON.

Figure No:

FIGURE 1



2.0 Design Requirements for Approval

The Town of St. Marys as part of the Site Plan Approval for the development requires the proposed development to meet the following stormwater management design requirements:

Stormwater Quantity Control Requirement

In accordance with Section 6.2.4 of the May 2017 Town of St. Marys Engineering Design Guidelines and Supplemental Specifications for Municipal Services, the post development peak flow rates are to be controlled to the corresponding predevelopment (allowable) peak flow rates for the 2 year through to the 250 year storm events.

Stormwater Quality Control Requirement

In accordance with Section 6. required "Enhanced" Level of treatment as defined in the Ministry of the Environment, Conservation and Parks (MECP) Stormwater Management Planning and Design Manual. It is recommended that the proposed site be designed to promote natural removal of sediment for post 2.1 of the Town of St. Marys Engineering Design Guidelines and Supplemental Specifications for Municipal Services, the post development flows are to be designed to meet the development flows.

3.0 Stormwater Management Design

3.1 Design Approach

Calculation Method

In accordance with Section 5.3 of the Town of St. Marys Engineering Design Guidelines and Supplemental Specifications for Municipal Services, rational method calculations are required. Therefore, GRIT will use the rational method calculations to review the predevelopment (allowable) and post development peak flow rates. When using the rational method calculations, The Town of St. Marys requires the use of time of concentration from Section 5.3.2, and runoff coefficient parameters from Section 5.3.3. When using the rational method calculations, GRIT recommends the runoff coefficients be increased 10% for the 25 year storm, 20% for the 50 year storm, and 25% for the 100 year storm events.

Site Review Methodology

To complete a stormwater management design for the development that achieves the previously noted requirements set forth by the Town of St. Marys, GRIT will complete the following:

- Review of the existing drainage and overland flow route patterns and site characteristics.
- Calculate the predevelopment (allowable) runoff coefficients and peak flow rates for the 2, 5, 10, 25, 50, 100 and 250 year storm events.
- Calculate the post development runoff coefficients and peak flow rates for the 2, 5, 10, 25, 50, 100 and 250 year storm events.
- Determine the onsite quantity control structures based on proposed site characteristics and accurately calculate the size requirements.
- Determine the required onsite stormwater storage volume and surface ponding elevations.
- Review and evaluate stormwater quality control techniques and structures.

3.2 Predevelopment Condition

In a predevelopment condition the site is comprised of a residential building, shed and garage/barn, gravel parking areas, and vegetated areas. The Site generally slopes to the northwest corner of the property.

Stormwater minor and major flows are directed overland towards the northwest of the site. Those flows then continue northwesterly where it is intercepted at the northwest

grocery store. External flows to the south of the site flow overland on the cultivated field towards an existing drainage draw southwest of the site.

Figure 2 illustrates the predevelopment catchment areas, the site characteristics analysis, existing drainage and overland flow pattern.

3.3 Post Development Condition

In the ultimate post development condition, the site is comprised of six self-storage buildings and outside gravel storage area, two residential buildings, gravel parking areas, and vegetated areas. Figure 3 illustrates the proposed ultimate site and the site characteristics analysis chart.

Controlled stormwater minor flows are directed through on site swales and a private storm sewer. Flows are intercepted at a rear grassed swale to the west of the site where stormwater major flows will be overcontrolled and ultimately discharged at the northwest portion of the site.

Uncontrolled flows for minor and major flows will maintain the existing drainage patterned and outlet towards the northern site boundary.

3.4 Quantity Control Summary

To meet the stormwater management quantity control criteria as noted in Section 2 of this report, a 200mm diameter PVC storm pipe will be installed in the storm ditch inlet catchbasin with a 190mm orifice installed (ST-DICB 10) at elevation 325.04m. Sufficient stormwater retention volumes will be provided for the major storm events, while being controlled by the proposed outlet. A 1.3m wide turfstone weir will be installed at an elevation of 325.75m to allow for flows over the 10 year to outlet while maintaining predevelopment flows. Discharge from the weir will be directed over a rip rap spillway toward the northwest corner of the site.

To accommodate the reduced minor and major stormwater flows, the underground storm infrastructure and proposed grading (surface storage) will be used to provide the stormwater retention volumes required. Refer to Appendix A for stage storage discharge and proposed design calculations.

Figure 4 illustrates the location of the proposed stormwater controls, proposed ponding elevations and a design summary chart.

3.5 Quality Control Summary

To meet the recommended stormwater management quality control criteria, as noted in Section 2 of this report, low lot level grassed retention area and a 1200mm diameter First




Defense, model FD-4HC oil grit separator or approved equivalent is proposed for the development. The FD-4HC (ST-OGS 11) is proposed to be installed inline and downstream from the proposed orifice and provides 84.0% removal of total suspended solids (TSS).

Refer to Appendix B for oil grit separator sizing summary, typical details and Operations and Maintenance information.

3.6 Erosion & Sedimentation Control

Erosion and sediment controls are proposed for the site design as illustrated on GRIT Engineering Drawing C300 and further detailed on C500. The proposed measures include sediment control fencing and sediment silt sacs to be installed prior to the start of any construction and maintained with regular maintenance by the contractor until the development is complete with final surface and vegetation stabilized with mature growth.

CATCHMENT AREA CHARACTERISTICS						
CATCHMENT	AREA (m ²)	BUILDING (m ²)	LANDSCAPED (m ²)	ASP/CONC. (m ²)	GRAVEL (m ²)	PERCENT IMPERVIOUS (m ²)
101	15,668.61	265.12	15,104.47		299.02	13.0%
102	2,850.93	102.70	2,748.23			13.2%
Total	18,519.54	367.82	17,852.70	0.00	299.02	




ROAD 120

SCALE 1:1000

GRIT
ENGINEERING

169 HURON STREET
STRATFORD, ON
N5A 5S9
www.gritengineering.ca

Legend

- CATCHMENT 101 
- CATCHMENT PARAMETER 
- EX. OVERLAND FLOW ROUTE 


Project:
ROAD 120
SELF STORAGE UNITS

Figure Title:
PREDEVELOPMENT
CATCHMENTS

Figure No:
FIGURE 2

file: y:\project\work\fig2\121_self storage, road 120 st\mxy\k-drawings\working\drawings\sheet\sefig021-21-self-storage.dwg by: margspc 2021-12-20

CATCHMENT AREA CHARACTERISTICS						
CATCHMENT	AREA (m ²)	BUILDING (m ²)	LANDSCAPED (m ²)	ASP/CONC. (m ²)	GRAVEL (m ²)	PERCENT IMPERVIOUS (m ²)
102	2,850.93	102.70	2,748.23			13.2%
201	2,071.14	175.06	1,706.50		189.58	24.9%
202	13,597.47	2,774.40	2,640.59		8,182.48	76.5%
Total	18,519.54	3,052.16	7,095.32	0.00	8,372.06	



SCALE 1:750

GRIT
ENGINEERING

169 HURON STREET
STRATFORD, ON
N5A 5S9
www.gritengineering.ca

Legend

- CATCHMENT BOUNDARY
- CATCHMENT PARAMETER 201
0.123
- EX. OVERLAND FLOW ROUTE


- PROPOSED SWALE 0.2%
- PROPOSED STORM SEWER

Project:
**ROAD 120
SELF STORAGE UNITS**

Figure Title:
**POST DEVELOPMENT
CATCHMENTS**

Figure No:
FIGURE 3

file: y:\project\work\fig021-21_self storage, road 120 st manyok-drawing\working drawings\sheet set\fig021-21-self-storage.dwg by: margoc 2021-12-20



Design Summary										
Storm Event (Yr)	Uncontrolled Flow (L/s)	Controlled Flow			Total Post Flow (L/s)	Total Pre Flow (L/s)	Ponding Elevation (m)	Storage Required (m3)	Ponding Volume (m3)	Ponding Depth (m)
		Orifice Flow (L/s)	Weir Flow (L/s)	Total Flow (L/s)						
2	27.57	50.76	0.00	50.76	78.33	87.67	325.56	115.98	145.36	0.52
5	35.81	55.33	0.00	55.33	91.15	113.88	325.64	187.88	192.09	0.60
10	41.28	59.55	0.00	59.55	100.83	131.27	325.72	239.29	241.48	0.68
25	52.97	65.38	21.76	87.14	140.11	168.43	325.84	297.46	320.58	0.80
50	63.50	68.99	56.49	87.14	188.98	201.92	325.92	327.98	376.68	0.88
100	69.44	70.72	77.56	148.29	217.73	220.82	325.96	348.45	405.75	0.92
250	83.18	72.42	100.75	173.17	256.34	264.50	326.00	426.74	435.51	0.96

SCALE 1:500



Legend

- PROPOSED STORM SEWER
- PROPOSED STORM STRUCTURE
- PROPOSED SWALE
- PROPOSED 5 YEAR PONDING ELEVATION
- PROPOSED 250 YEAR PONDING ELEVATION

- EX. STORM SEWER
- EX. SANITARY SEWER
- EX. WATERMAIN
- EX. MH
- EX. FH
- EX. VALVE

Project:
ROAD 120
SELF STORAGE UNITS

Figure Title:
STORMWATER MANAGEMENT SKETCH

Figure No:
FIGURE 4

file: y:\project\work\fig02-121_self storage, road 120 st manyok-drawing\working drawings\sheet design\02-121-self storage.dwg by: margoc 2021-12-20

4.0 Design Summary

- 4.1 The predevelopment and post development characteristics of the site were analyzed and an increase in imperviousness was calculated in the post development condition and therefore quantity control will be required.
- 4.2 The proposed 190mm diameter orifice stormwater control in ditch inlet catchbasin ST-DICB 10 will restrict the post development peak flows to less than the allowable peak flow for the 2 year through to the 250 year storm event utilizing the available stormwater retention.
- 4.3 A 1.3m wide Turfstone weir will be installed at an elevation of 325.75m to discharge additional predevelopment flows over the 10 year design storm.
- 4.4 The post development minor and major stormwater flows will outlet to the northwest of the site over a rip rap spillway.
- 4.5 The proposed low lot level dry retention area and sumps should provide adequate natural sedimentation to occur in addition to a proposed oil grit separator model FD-4HC by ADS Canada or approved equivalent to provide the required MECP 'Enhanced' quality control requirements.

5.0 Design Recommendations

The proposed design recommends the following be installed and constructed in accordance with the GRIT Engineering drawings located in Appendix B:

- 5.1 Install a 190mm diameter orifice in ditch inlet catchbasin ST-DICB 10, at an elevation of 325.04m, as shown on drawing C300 and further detailed on C500;
- 5.2 Construct a 1.3m wide Turfstone weir at an elevation of 325.75m to discharge additional pre-development flows over the 10 year design storm;
- 5.3 Construct an oil grit separator (ST-OGS 11) downstream of ST-DICB 10 to provide "Enhanced" level of treatment for the site;
- 5.4 Construct the proposed site grading to provide the required stormwater retention volume as shown on drawing C300; and
- 5.5 Install the proposed erosion and sediment control measures as shown on drawing C300 and further detailed on C500.

Yours respectfully,

GRIT Engineering Inc.



Dan Santos, C.Tech
Designer

Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Founder & CEO



Appendix A

Stormwater Quantity Control Calculations

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Rainfall Intensity Formula

$$I = A/(B+t)^C$$

A =IDF Parameter
B =IDF Parameter
C =IDF Parameter
t =Time (Min.)

Modified Rational Method Formula

$$Q = kCIA$$

k =2.78
C =Runoff coefficient
I =Rainfall intensity (mm/hr)
A =Contribution area (ha)

Online Orifice

$$Q = Ca\sqrt{2gh}$$

C =Discharge Coefficient
a =Cross sectional area of orifice (m²)
g =Constant of Gravitational Pull (9.81 m/s²)
h =Total Head (m)

Weir

Rectangular

$$Q = cLH^{3/2}$$

c =Discharge Coefficient
L =Length of Weir (m)
H =Maximum head (m)

Rainfall Parameters: Stratford

Rainfall Event	A	B	C
2 Year	601.090	4.922	0.767
5 Year	875.105	7.641	0.762
10 Year	1062.156	9.025	0.760
25 Year	1319.273	10.500	0.762
50 Year	1560.739	12.129	0.767
100 Year	1821.990	13.507	0.773
250 Year	2095.179	13.509	0.773

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Catchment Number: Catchment 101 - Outlets to NW corner of site

Catchment Characteristics:

Surface Material	Area (m2) (A)	Percent Impervious	Coefficient (C)
Building	265.12	100%	0.90
Asphalt / Concrete	-	100%	0.90
Gravel	299.02	90%	0.90
Grass	15,104.48	10%	0.20
Total / Average	15,668.62	13.0%	0.23

Rainfall Event (Year)	A	B	C	t (min)	Intensity (mm/hr)	C' Multiplier	C	Q (L/s)
2	601.090	4.922	0.767	10	75.616	1.00	0.23	74.18
5	875.105	7.641	0.762	10	98.22	1.00	0.23	96.35
10	1062.156	9.025	0.760	10	113.21	1.00	0.23	111.06
25	1319.273	10.500	0.762	10	132.06	1.10	0.25	142.50
50	1560.739	12.129	0.767	10	145.13	1.20	0.27	170.83
100	1821.990	13.507	0.773	10	158.71	1.20	0.27	186.83
250	2095.179	13.509	0.773	10	182.50	1.25	0.28	223.78

Catchment Number: Catchment 102 - Outlets to NW corner of site

Catchment Characteristics:

Surface Material	Area (m2) (A)	Percent Impervious	Coefficient (C)
Building	102.70	100%	0.90
Asphalt / Concrete	-	100%	0.90
Gravel	-	90%	0.90
Grass	2,748.23	10%	0.20
Total / Average	2,850.93	13.2%	0.23

Rainfall Event (Year)	A	B	C	t (min)	Intensity (mm/hr)	C' Multiplier	C	Q (L/s)
2	601.090	4.922	0.767	10	75.616	1.00	0.23	13.50
5	875.105	7.641	0.762	10	98.22	1.00	0.23	17.53
10	1062.156	9.025	0.760	10	113.21	1.00	0.23	20.21
25	1319.273	10.500	0.762	10	132.06	1.10	0.25	25.93
50	1560.739	12.129	0.767	10	145.13	1.20	0.27	31.09
100	1821.990	13.507	0.773	10	158.71	1.20	0.27	34.00
250	2095.179	13.509	0.773	10	182.50	1.25	0.28	40.72

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Uncontrolled Catchment: Catchment 102 & 201 - Outlets to NW corner of site

Catchment Characteristics:

Surface Material	Area (m2) (A)	Percent Impervious	Coefficient (C)
Building	277.76	100%	0.90
Asphalt / Concrete	-	100%	0.90
Gravel	189.58	90%	0.90
Grass	4,454.73	20%	0.20
Total / Average	4,922.07	27.2%	0.27

Rainfall Event (Year)	A	B	C	t (min)	Intensity (mm/hr)	C' Multiplier	C	Q (L/s)
2	601.090	4.922	0.767	10	75.616	1.00	0.27	27.57
5	875.105	7.641	0.762	10	98.22	1.00	0.27	35.81
10	1062.156	9.025	0.760	10	113.21	1.00	0.27	41.28
25	1319.273	10.500	0.762	10	132.06	1.10	0.29	52.97
50	1560.739	12.129	0.767	10	145.13	1.20	0.32	63.50
100	1821.990	13.507	0.773	10	158.71	1.20	0.32	69.44
250	2095.179	13.509	0.773	10	182.50	1.25	0.33	83.18

Controlled Catchment: Catchment 202 - Outlets to NW corner of site

Catchment Characteristics:

Surface Material	Area (m2) (A)	Percent Impervious	Coefficient (C)
Building	2,774.40	100%	0.90
Asphalt / Concrete	-	100%	0.90
Gravel	8,182.48	90%	0.90
Grass	2,640.59	20%	0.20
Total / Average	13,597.47	78.4%	0.76

Rainfall Event (Year)	A	B	C	t (min)	Intensity (mm/hr)	C' Multiplier	C	Q (L/s)
2	601.090	4.922	0.767	10	75.616	1.00	0.76	218.40
5	875.105	7.641	0.762	10	98.22	1.00	0.76	283.69
10	1062.156	9.025	0.760	10	113.21	1.00	0.76	326.99
25	1319.273	10.500	0.762	10	132.06	1.10	0.84	419.57
50	1560.739	12.129	0.767	10	145.13	1.20	0.92	502.99
100	1821.990	13.507	0.773	10	158.71	1.20	0.92	550.08
250	2095.179	13.509	0.773	10	182.50	1.25	0.96	658.87

Project No.: GE021-21
 Project Name: Road 120 Self Storage
 Project Location: St. Mary
 Designer: Dan Santos, C.Tech
 Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
 Date: 15-Dec-21

Stage Storage Discharge Pond Characteristics

Top of Grate Elevation= 325.04 m
 Max Ponding Elevation= 326.00 m
 Elevation Increment= 0.04 m
 No of Stages= 25
 Volume in Structures= 3.5 m³

Stage Storage Discharge			
Stage	Elevation (m)	Surface Volume (m ³)	Total Volume (m ³)
1	325.04	0.00	3.50
2	325.08	0.20	3.70
3	325.12	1.33	4.83
4	325.16	3.74	7.24
5	325.20	7.74	11.24
6	325.24	13.56	17.06
7	325.28	21.42	24.92
8	325.32	31.48	34.98
9	325.36	43.96	47.46
10	325.40	59.07	62.57
11	325.44	77.03	80.53
12	325.48	97.74	101.24
13	325.52	119.47	122.97
14	325.56	141.86	145.36
15	325.60	164.90	168.40
16	325.64	188.59	192.09
17	325.68	212.95	216.45
18	325.72	237.98	241.48
19	325.76	263.67	267.17
20	325.80	290.04	293.54
21	325.84	317.08	320.58
22	325.88	344.79	348.29
23	325.92	373.18	376.68
24	325.96	402.25	405.75
25	326.00	432.01	435.51
26			
27			
28			
29			
30			

Design Summary										
Storm Event (Yr)	Uncontrolled Flow (L/s)	Controlled Flow			Total Post Flow (L/s)	Total Pre Flow (L/s)	Ponding Elevation (m)	Storage Required (m3)	Ponding Volume (m3)	Ponding Depth (m)
		Orifice Flow (L/s)	Weir Flow (L/s)	Total Flow (L/s)						
2	27.57	50.76	0.00	50.76	78.33	87.67	325.56	115.98	145.36	0.52
5	35.81	55.33	0.00	55.33	91.15	113.88	325.64	187.88	192.09	0.60
10	41.28	59.55	0.00	59.55	100.83	131.27	325.72	239.29	241.48	0.68
25	52.97	65.38	21.76	87.14	140.11	168.43	325.84	297.46	320.58	0.80
50	63.50	68.99	56.49	87.14	188.98	201.92	325.92	327.98	376.68	0.88
100	69.44	70.72	77.56	148.29	217.73	220.82	325.96	348.45	405.75	0.92
250	83.18	72.42	100.75	173.17	256.34	264.50	326.00	426.74	435.51	0.96

Online Orifice = $C_a \sqrt{2gh}$

Orifice Diameter= 190.00 mm
 Invert Elevation= 325.04 m
 Orifice Area= 0.0284 m²
 Weir Coefficient= 0.62

Weir = $cLH^{3/2}$

Elevation= 325.75
 c= 0.62
 L= 1.30
 H= Varies



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 2 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 87.67 L/s
Proposed Flow Rate 78.33 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.52 m
Flow	50.76 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.27	0.76

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.00 m
Flow	0 L/s

IDF Parameters		
A	B	C
601.090	4.922	0.767

Total Controlled Flow= 50.76 L/s

Storage Required=	115.98 m ³
Storage Available=	145.36 m ³
Ponding Elevation=	325.56 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	75.62	27.57	218.40	100.58	78.33
15	60.58	22.09	174.98	111.79	72.85
20	51.02	18.60	147.36	115.92	69.36
25	44.35	16.17	128.08	115.98	66.93
30	39.39	14.36	113.77	113.41	65.12
35	35.55	12.96	102.67	109.01	63.72
40	32.47	11.84	93.79	103.26	62.60
45	29.95	10.92	86.49	96.48	61.68
50	27.83	10.15	80.39	88.88	60.91
55	26.03	9.49	75.19	80.62	60.25
60	24.48	8.93	70.71	71.81	59.69
65	23.13	8.43	66.80	62.54	59.19
70	21.93	8.00	63.35	52.87	58.76
75	20.87	7.61	60.29	42.87	58.37
80	19.92	7.26	57.55	32.57	58.03
85	19.07	6.95	55.08	22.00	57.71
90	18.29	6.67	52.84	11.20	57.43



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 5 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 113.88 L/s
Proposed Flow Rate 91.15 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.60 m
Flow	55.33 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.27	0.76

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.00 m
Flow	0 L/s

IDF Parameters		
A	B	C
875.105	7.641	0.762

Total Controlled Flow= 55.33 L/s

Storage Required=	187.88 m ³
Storage Available=	192.09 m ³
Ponding Elevation=	325.64 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	98.22	35.81	283.69	137.01	91.15
15	81.21	29.61	234.56	161.31	84.94
20	69.76	25.43	201.48	175.37	80.77
25	61.46	22.41	177.50	183.25	77.74
30	55.13	20.10	159.23	187.02	75.43
35	50.13	18.28	144.80	187.88	73.61
40	46.07	16.80	133.07	186.56	72.13
45	42.70	15.57	123.32	183.57	70.90
50	39.85	14.53	115.08	179.25	69.86
55	37.40	13.64	108.02	173.85	68.97
60	35.27	12.86	101.88	167.55	68.19
65	33.41	12.18	96.49	160.50	67.51
70	31.75	11.58	91.72	152.81	66.91
75	30.28	11.04	87.46	144.55	66.37
80	28.95	10.56	83.63	135.81	65.89
85	27.76	10.12	80.17	126.65	65.45
90	26.67	9.72	77.02	117.10	65.06



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 10 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 131.27 L/s
Proposed Flow Rate 100.83 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.68 m
Flow	59.55 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.27	0.76

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.00 m
Flow	0 L/s

IDF Parameters		
A	B	C
1062.156	9.025	0.760

Total Controlled Flow= 59.55 L/s

Storage Required=	239.29 m ³
Storage Available=	241.48 m ³
Ponding Elevation=	325.72 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	113.21	41.28	326.99	160.46	100.83
15	94.82	34.57	273.85	192.87	94.13
20	82.13	29.94	237.20	213.17	89.50
25	72.78	26.54	210.21	225.98	86.09
30	65.58	23.91	189.41	233.74	83.47
35	59.84	21.82	172.83	237.87	81.37
40	55.14	20.10	159.26	239.29	79.66
45	51.22	18.67	147.93	238.61	78.23
50	47.89	17.46	138.30	236.25	77.01
55	45.02	16.41	130.02	232.52	75.97
60	42.52	15.50	122.79	227.66	75.06
65	40.31	14.70	116.44	221.84	74.25
70	38.36	13.99	110.79	215.21	73.54
75	36.61	13.35	105.75	207.87	72.90
80	35.04	12.78	101.20	199.91	72.33
85	33.61	12.26	97.09	191.41	71.81
90	32.32	11.78	93.34	182.42	71.34



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 25 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 168.43 L/s
Proposed Flow Rate 140.11 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.80 m
Flow	65.38 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.29	0.84

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.09 m
Flow	21.762 L/s

IDF Parameters		
A	B	C
1319.273	10.500	0.762

Total Controlled Flow= 87.14 L/s

Storage Required=	297.46 m ³
Storage Available=	320.58 m ³
Ponding Elevation=	325.84 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	132.06	52.97	419.57	199.46	140.11
15	111.83	44.85	355.28	241.33	131.99
20	97.57	39.13	309.97	267.40	126.27
25	86.91	34.86	276.11	283.46	122.00
30	78.61	31.53	249.73	292.67	118.67
35	71.93	28.85	228.54	296.93	115.99
40	66.44	26.65	211.08	297.46	113.79
45	61.83	24.80	196.43	295.08	111.94
50	57.89	23.22	183.93	290.38	110.36
55	54.50	21.86	173.13	283.78	109.00
60	51.52	20.67	163.70	275.60	107.81
65	48.90	19.61	155.37	266.09	106.75
70	46.57	18.68	147.96	255.44	105.82
75	44.48	17.84	141.32	243.81	104.98
80	42.60	17.08	135.33	231.31	104.22
85	40.89	16.40	129.90	218.06	103.54
90	39.33	15.77	124.94	204.13	102.91



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 50 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 201.92 L/s
Proposed Flow Rate 188.98 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.88 m
Flow	68.99 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.32	0.92

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.17 m
Flow	56.4948 L/s

IDF Parameters		
A	B	C
1560.739	12.129	0.767

Total Controlled Flow= 125.48 L/s

Storage Required=	327.98 m ³
Storage Available=	376.68 m ³
Ponding Elevation=	325.92 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	145.13	63.50	502.99	226.50	188.98
15	124.13	54.31	430.23	274.27	179.79
20	109.03	47.70	377.88	302.88	173.19
25	97.58	42.69	338.20	319.08	168.18
30	88.57	38.75	306.97	326.67	164.23
35	81.27	35.56	281.66	327.98	161.04
40	75.22	32.91	260.70	324.52	158.39
45	70.12	30.68	243.02	317.34	156.16
50	65.75	28.77	227.87	307.16	154.25
55	61.96	27.11	214.74	294.53	152.59
60	58.64	25.65	203.22	279.86	151.14
65	55.70	24.37	193.04	263.47	149.85
70	53.08	23.22	183.96	245.61	148.71
75	50.73	22.19	175.81	226.46	147.68
80	48.60	21.26	168.44	206.21	146.75
85	46.67	20.42	161.75	184.97	145.90
90	44.91	19.65	155.64	162.86	145.13



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 100 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 220.82 L/s
Proposed Flow Rate 217.73 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.92 m
Flow	70.72 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.32	0.92

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.21 m
Flow	77.5647 L/s

IDF Parameters		
A	B	C
1821.990	13.507	0.773

Total Controlled Flow= 148.29 L/s

Storage Required=	348.45 m ³
Storage Available=	405.75 m ³
Ponding Elevation=	325.96 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	158.71	69.44	550.08	241.07	217.73
15	136.73	59.82	473.89	293.05	208.11
20	120.67	52.80	418.24	323.95	201.09
25	108.37	47.42	375.61	340.98	195.71
30	98.61	43.15	341.78	348.29	191.44
35	90.66	39.67	314.22	348.45	187.96
40	84.04	36.77	291.27	343.16	185.06
45	78.43	34.32	271.84	333.58	182.61
50	73.61	32.21	255.14	320.55	180.50
55	69.43	30.38	240.62	304.70	178.66
60	65.75	28.77	227.87	286.49	177.05
65	62.49	27.34	216.57	266.29	175.63
70	59.57	26.07	206.47	244.38	174.35
75	56.96	24.92	197.40	221.00	173.21
80	54.59	23.88	189.19	196.32	172.17
85	52.43	22.94	181.72	170.51	171.23
90	50.46	22.08	174.90	143.70	170.37



STORMWATER MANAGEMENT CALCULATIONS

PROPOSED DEVELOPMENT - 250 YEAR SWM

Project No.: GE021-21
Project Name: Road 120 Self Storage
Project Location: St. Mary
Designer: Dan Santos, C.Tech
Engineer: Montana Wilson, EMBA, M.Eng, P.Eng, PMP
Date: 15-Dec-21

Predevelopment Flow Rate 264.50 L/s
Proposed Flow Rate 256.34 L/s

Orifice Details	
Size	190.00 mm
Elevation	325.04 m
Area	0.0284 m ²
Coefficient	0.62
Head	0.96 m
Flow	72.42 L/s

Catchment Characteristics		
	Uncontrolled Catchment	Controlled Catchment
Area (Ha) (A)	0.49	1.36
Coefficient (C)	0.33	0.96

Weir Details	
Elevation	325.75 m
Coefficient	0.62
Length	1.3 m
Head	0.25 m
Flow	100.75 L/s

IDF Parameters		
A	B	C
2095.179	13.509	0.773

Total Controlled Flow= 173.17 L/s

Storage Required=	426.74 m ³
Storage Available=	435.51 m ³
Ponding Elevation=	326.00 m

Design Chart					
Time (min)	Intensity (I) (mm/hr) (A/(B+t) C)	Uncontrolled Flow (L/s) (=2.78CIA)	Controlled Flow (L/s) (=2.78CIA)	Storage Volume Required	Total Site Flow (L/s)
10	182.50	83.18	658.87	291.42	256.34
15	157.22	71.66	567.63	355.01	244.83
20	138.76	63.24	500.97	393.36	236.41
25	124.62	56.80	449.91	415.11	229.96
30	113.40	51.68	409.39	425.21	224.85
35	104.25	47.51	376.38	426.74	220.68
40	96.64	44.04	348.89	421.73	217.21
45	90.19	41.11	325.61	411.60	214.27
50	84.65	38.58	305.61	397.33	211.75
55	79.83	36.39	288.22	379.68	209.55
60	75.60	34.46	272.95	359.21	207.63
65	71.85	32.75	259.41	336.35	205.92
70	68.50	31.22	247.32	311.45	204.39
75	65.49	29.85	236.45	284.77	203.02
80	62.77	28.61	226.62	256.56	201.78
85	60.29	27.48	217.67	226.98	200.65
90	58.03	26.45	209.50	196.19	199.62



Appendix B

Oil Grit Sizing Summary

ADS OGS Sizing Summary

Project Name:	60 Road 120	
Consulting Engineer:	GRIT Engineering	
Location:	St. Mary's, ON	
Sizing Completed By:	C. Neath	Email: cody.neath@ads-pipe.com


Treatment Requirements		
Treatment Goal:	Enhanced (MOE)	
Selected Parameters:	80% TSS	90% Volume
Selected Unit:	FD-4HC	

Site Details	
Site Area:	1.28 ha
% Impervious:	82%
Rational C:	0.79
Rainfall Station:	Stratford, ONT
Particle Size Distribution:	Fine
Peak Flowrate:	90 L/s

Summary of Results		
Model	TSS Removal	Volume Treated
FD-4HC	84.0%	99.1%
FD-5HC	88.0%	99.6%
FD-6HC	90.0%	99.9%
FD-8HC	94.0%	99.9%

FD-4HC Specification	
Unit Diameter (A):	1,200 mm
Inlet Pipe Diameter (B):	300 mm
Outlet Pipe Diameter (C):	300 mm
Height, T/G to Outlet Invert (D):	1460 mm
Height, Outlet Invert to Sump (E):	1515 mm
Sediment Storage Capacity (F):	0.78 m ³
Oil Storage Capacity (G):	723 L
Recommended Sediment Depth for Maintenance:	440 mm
Max. Pipe Diameter:	600 mm
Peak Flow Capacity:	510 L/s

Site Elevations:	
Rim Elevation:	326.51
Inlet Pipe Elevation:	325.05
Outlet Pipe Elevation:	325.05



Notes:

Removal efficiencies are based on NJDEP Test Protocols and independently verified.

All units supplied by ADS have numerous local, provincial, and international certifications (copies of which can be provided upon request). The design engineer is responsible for ensuring compliance with applicable regulations.




Project Name: 60 Road 120
 Consulting Engineer: GRIT Engineering
 Location: St. Mary's, ON

Net Annual Removal Efficiency Summary: FD-4HC

Rainfall Intensity ⁽¹⁾	Fraction of Rainfall ⁽¹⁾	FD-4HC Removal Efficiency ⁽²⁾	Weighted Net-Annual Removal Efficiency
mm/hr	%	%	%
0.50	0.3%	100.0%	0.3%
1.00	15.5%	94.4%	14.7%
1.50	14.3%	90.9%	13.0%
2.00	13.6%	88.5%	12.0%
2.50	4.0%	86.7%	3.5%
3.00	2.3%	85.3%	2.0%
3.50	8.4%	84.1%	7.1%
4.00	4.6%	83.0%	3.9%
4.50	1.7%	82.1%	1.4%
5.00	4.8%	81.3%	3.9%
6.00	3.8%	79.9%	3.0%
7.00	4.2%	78.8%	3.3%
8.00	3.0%	77.8%	2.3%
9.00	2.2%	77.0%	1.7%
10.00	2.3%	76.2%	1.8%
20.00	9.3%	71.5%	6.7%
30.00	2.8%	68.8%	2.0%
40.00	1.2%	67.0%	0.8%
50.00	0.6%	65.6%	0.4%
100.00	0.8%	61.5%	0.5%
150.00	0.1%	59.3%	0.1%
200.00	0.0%	57.7%	0.0%
Total Net Annual Removal Efficiency:			84.0%
Total Runoff Volume Treated:			99.1%

Notes:

- (1) Rainfall Data: 1965:2007, HLY03, Stratford, ON, 6148105.
- (2) Based on third party verified data and approximating the removal of a PSD similar to the STC Fine distribution
- (3) Rainfall adjusted to 5 min peak intensity based on hourly average.



Operation and Maintenance Manual

First Defense[®] High Capacity and First Defense[®] Optimum

Vortex Separator for Stormwater Treatment

Table of Contents

3	FIRST DEFENSE® BY HYDRO INTERNATIONAL <ul style="list-style-type: none">- INTRODUCTION- OPERATION- POLLUTANT CAPTURE AND RETENTION
4	MODEL SIZES & CONFIGURATIONS <ul style="list-style-type: none">- FIRST DEFENSE® COMPONENTS
5	MAINTENANCE <ul style="list-style-type: none">- OVERVIEW- MAINTENANCE EQUIPMENT CONSIDERATIONS- DETERMINING YOUR MAINTENANCE SCHEDULE
6	MAINTENANCE PROCEDURES <ul style="list-style-type: none">- INSPECTION- FLOATABLES AND SEDIMENT CLEAN OUT
8	FIRST DEFENSE® INSTALLATION LOG
9	FIRST DEFENSE® INSPECTION AND MAINTENANCE LOG

COPYRIGHT STATEMENT: The contents of this manual, including the graphics contained herein, are intended for the use of the recipient to whom the document and all associated information are directed. Hydro International plc owns the copyright of this document, which is supplied in confidence. It must not be used for any purpose other than that for which it is supplied and must not be reproduced, in whole or in part stored in a retrieval system or transmitted in any form or by any means without prior permission in writing from Hydro International plc. First Defense® is a trademarked hydrodynamic vortex separation device of Hydro International plc. A patent covering the First Defense® has been granted.

DISCLAIMER: Information and data contained in this manual is exclusively for the purpose of assisting in the operation and maintenance of Hydro International plc's First Defense®. No warranty is given nor can liability be accepted for use of this information for any other purpose. Hydro International plc has a policy of continuous product development and reserves the right to amend specifications without notice.

I. First Defense® by Hydro International

Introduction

The First Defense® is an enhanced vortex separator that combines an effective and economical stormwater treatment chamber with an integral peak flow bypass. It efficiently removes total suspended solids (TSS), trash and hydrocarbons from stormwater runoff without washing out previously captured pollutants. The First Defense® is available in several model configurations to accommodate a wide range of pipe sizes, peak flows and depth constraints.

The two product models described in this guide are the First Defense® High Capacity and the First Defense® Optimum; they are inspected and maintained identically.

Operation

The First Defense® operates on simple fluid hydraulics. It is self-activating, has no moving parts, no external power requirement and is fabricated with durable non-corrosive components. No manual procedures are required to operate the unit and maintenance is limited to monitoring accumulations of stored pollutants and periodic clean-outs. The First Defense® has been designed to allow for easy and safe access for inspection, monitoring and clean-out procedures. Neither entry into the unit nor removal of the internal components is necessary for maintenance, thus safety concerns related to confined-space-entry are avoided.

Pollutant Capture and Retention

The internal components of the First Defense® have been designed to optimize pollutant capture. Sediment is captured and retained in the base of the unit, while oil and floatables are stored on the water surface in the inner volume (Fig.1).

The pollutant storage volumes are isolated from the built-in bypass chamber to prevent washout during high-flow storm events. The sump of the First Defense® retains a standing water level between storm events. This ensures a quiescent flow regime at the onset of a storm, preventing resuspension and washout of pollutants captured during previous events.

Accessories such as oil absorbent pads are available for enhanced oil removal and storage. Due to the separation of the oil and floatable storage volume from the outlet, the potential for washout of stored pollutants between clean-outs is minimized.

Applications

- Stormwater treatment at the point of entry into the drainage line
- Sites constrained by space, topography or drainage profiles with limited slope and depth of cover
- Retrofit installations where stormwater treatment is placed on or tied into an existing storm drain line
- Pretreatment for filters, infiltration and storage

Advantages

- Inlet options include surface grate or multiple inlet pipes
- Integral high capacity bypass conveys large peak flows without the need for "offline" arrangements using separate junction manholes
- Long flow path through the device ensures a long residence time within the treatment chamber, enhancing pollutant settling
- Delivered to site pre-assembled and ready for installation




Fig.1 Pollutant storage volumes in the First Defense®.

II. Model Sizes & Configurations

The First Defense® inlet and internal bypass arrangements are available in several model sizes and configurations. The components have modified geometries allowing greater design flexibility to accommodate various site constraints.

All First Defense® models include the internal components that are designed to remove and retain total suspended solids (TSS), gross solids, floatable trash and hydrocarbons (Fig.2). First Defense® model sizes (diameter) are shown in Table 1.

III. Maintenance

First Defense® Components

- | | | |
|--------------------|-----------------------------|-------------------------|
| 1. Built-In Bypass | 4. Floatables Draw-off Port | 7. Sediment Storage |
| 2. Inlet Pipe | 5. Outlet Pipe | 8. Inlet Grate or Cover |
| 3. Inlet Chute | 6. Floatables Storage | |




Fig. 2

Table 1

First Defense® Model Sizes
(ft / m) diameter
3 / 0.9
4 / 1.2
5 / 1.5
6 / 1.8
7 / 2.1
8 / 2.4
10 / 3.0

Overview

The First Defense® protects the environment by removing a wide range of pollutants from stormwater runoff. Periodic removal of these captured pollutants is essential to the continuous, long-term functioning of the First Defense®. The First Defense® will capture and retain sediment and oil until the sediment and oil storage volumes are full to capacity. When sediment and oil storage capacities are reached, the First Defense® will no longer be able to store removed sediment and oil.

The First Defense® allows for easy and safe inspection, monitoring and clean-out procedures. A commercially or municipally owned sump-vac is used to remove captured sediment and floatables. Access ports are located in the top of the manhole.

Maintenance events may include Inspection, Oil & Floatables Removal, and Sediment Removal. Maintenance events do not require entry into the First Defense®, nor do they require the internal components of the First Defense® to be removed. In the case of inspection and floatables removal, a vactor truck is not required. However, a vactor truck is required if the maintenance event is to include oil removal and/or sediment removal.

Maintenance Equipment Considerations

The internal components of the First Defense® have a centrally located circular shaft through which the sediment storage sump can be accessed with a sump vac hose. The open diameter of this access shaft is 15 inches in diameter (Fig.3). Therefore, the nozzle fitting of any vactor hose used for maintenance should be less than 15 inches in diameter.




Fig.3 The central opening to the sump of the First Defense® is 15 inches in diameter.

Determining Your Maintenance Schedule

The frequency of clean out is determined in the field after installation. During the first year of operation, the unit should be inspected every six months to determine the rate of sediment and floatables accumulation. A simple probe such as a Sludge-Judge® can be used to determine the level of accumulated solids stored in the sump. This information can be recorded in the maintenance log (see page 9) to establish a routine maintenance schedule.

The vactor procedure, including both sediment and oil / floatables removal, for First Defense® typically takes less than 30 minutes and removes a combined water/oil volume of about 765 gallons.

Inspection Procedures

1. Set up any necessary safety equipment around the access port or grate of the First Defense® as stipulated by local ordinances. Safety equipment should notify passing pedestrian and road traffic that work is being done.
2. Remove the grate or lid to the manhole.
3. Without entering the vessel, look down into the chamber to inspect the inside. Make note of any irregularities. Fig.4 shows the standing water level that should be observed.
4. Without entering the vessel, use the pole with the skimmer net to remove floatables and loose debris from the components and water surface.
5. Using a sediment probe such as a Sludge Judge®, measure the depth of sediment that has collected in the sump of the vessel.
6. On the Maintenance Log (see page 9), record the date, unit location, estimated volume of floatables and gross debris removed, and the depth of sediment measured. Also note any apparent irregularities such as damaged components or blockages.
7. Securely replace the grate or lid.
8. Take down safety equipment.
9. Notify Hydro International of any irregularities noted during inspection.

Floatables and Sediment Clean Out

Floatables clean out is typically done in conjunction with sediment removal. A commercially or municipally owned sump-vac is used to remove captured sediment and floatables (Fig.4).

Floatables and loose debris can also be netted with a skimmer and pole. The access port located at the top of the manhole provides unobstructed access for a vactor hose to be lowered to the base of the sump.

Scheduling

- Floatables and sump clean out are typically conducted once a year during any season.
- Floatables and sump clean out should occur as soon as possible following a spill in the contributing drainage area.



Fig.4 Floatables are removed with a vactor hose

Recommended Equipment

- Safety Equipment (traffic cones, etc)
- Crow bar or other tool to remove grate or lid
- Pole with skimmer or net (if only floatables are being removed)
- Sediment probe (such as a Sludge Judge®)
- Vactor truck (flexible hose recommended)
- First Defense® Maintenance Log

Floatables and Sediment Clean Out Procedures

1. Set up any necessary safety equipment around the access port or grate of the First Defense® as stipulated by local ordinances. Safety equipment should notify passing pedestrian and road traffic that work is being done.
2. Remove the grate or lid to the manhole.
3. Without entering the vessel, look down into the chamber to inspect the inside. Make note of any irregularities.
4. Remove oil and floatables stored on the surface of the water with the vacator hose or with the skimmer or net
5. Using a sediment probe such as a Sludge Judge®, measure the depth of sediment that has collected in the sump of the vessel and record it in the Maintenance Log (page 9).
6. Once all floatables have been removed, drop the vacator hose to the base of the sump. Vacator out the sediment and gross debris off the sump floor
7. Retract the vacator hose from the vessel.
8. On the Maintenance Log provided by Hydro International, record the date, unit location, estimated volume of floatables and gross debris removed, and the depth of sediment measured. Also note any apparent irregularities such as damaged components, blockages, or irregularly high or low water levels.
9. Securely replace the grate or lid.

Maintenance at a Glance

Inspection	<ul style="list-style-type: none"> - Regularly during first year of installation - Every 6 months after the first year of installation
Oil and Floatables Removal	<ul style="list-style-type: none"> - Once per year, with sediment removal - Following a spill in the drainage area
Sediment Removal	<ul style="list-style-type: none"> - Once per year or as needed - Following a spill in the drainage area

NOTE: For most clean outs the entire volume of liquid does not need to be removed from the manhole. Only remove the first few inches of oils and floatables from the water surface to reduce the total volume of liquid removed during a clean out.



First Defense® Installation Log

HYDRO INTERNATIONAL REFERENCE NUMBER:	
SITE NAME:	
SITE LOCATION:	
OWNER:	CONTRACTOR:
CONTACT NAME:	CONTACT NAME:
COMPANY NAME:	COMPANY NAME:
ADDRESS:	ADDRESS:
TELEPHONE:	TELEPHONE:
FAX:	FAX:

INSTALLATION DATE: / /

MODEL SIZE (CIRCLE ONE): [3-FT] [4-FT] [5-FT] [6-FT] [7-FT] [8-FT] [10-FT]


INLET (CIRCLE ALL THAT APPLY): GRATED INLET (CATCH BASIN) INLET PIPE (FLOW THROUGH)





Appendix C

Design Drawings

PROPOSED FEATURES




EXISTING FEATURES



CONTRACTOR NOTE:
ALL STORM SEWER PIPING TO BE INSULATED WITH RIGID INSULATION PER DETAIL ON C500

CAUTION:
EXISTING BELL EASEMENT. LOCATE EXISTING UTILITIES BY HAND DIG OR VACC TRUCK PRIOR TO CONSTRUCTION.



CONTRACTOR NOTES:
CONTRACTORS MUST CHECK AND VERIFY ALL DIMENSIONS AND REPORT ANY ERRORS TO THE ENGINEER PRIOR TO COMMENCEMENT OF WORK.
ALL DRAWINGS SHALL REMAIN THE PROPERTY OF THE ENGINEER AND SHALL NOT BE REUSED WITHOUT THE ENGINEER'S WRITTEN PERMISSION.
DRAWING SHOULD NOT BE SCALED FOR DIMENSIONS PURPOSES.

BENCHMARK
ELEVATIONS ARE RELATED TO TOP SPINDLE OF FIRE HYDRANT ON THE NORTH SIDE OF QUEEN STREET AT THE CORNER OF QUEEN AND 120 ROAD.
ELEVATION: 235.88m

No.	ISSUED DESCRIPTION	DATE
1	ISSUED FOR CLIENT REVIEW	2021-11-12
2	ISSUED FOR SITE PLAN APPROVAL	2021-11-16
3	REVISED PER MUNICIPAL COMMENTS	2021-12-20
4		
5		



**ROAD 120
SELF STORAGE UNITS**

PROJECT INFORMATION: 60 ROAD 120, ST. MARYS, ONTARIO

C & C MANAGEMENT

CLIENT INFORMATION:

**SITE SERVICING, GRADING,
AND EROSION & SEDIMENT
CONTROL PLAN**

DRAWING NAME: **GE021-21**

PROJECT No: **GE021-21**

DRAWING No: **C300**

SCALE: **1:300**

SHEET SET No: **3 of 4**

GENERAL NOTES AND CONSTRUCTION SPECIFICATIONS

1. GENERAL NOTES

- THESE PLANS ARE NOT FOR CONSTRUCTION UNTIL SIGNED AND SEALED BY ENGINEER AND APPROVED BY THE TOWN OF ST. MARYS.
- ALL CONSTRUCTION WORK TO BE COMPLETED IN ACCORDANCE WITH ALL APPLICABLE (MOST RECENT) STANDARDS.
- THE PLANS PREPARED BY GRIT ENGINEERING INC. ARE NOT TO BE USED FOR CONSTRUCTION UNTIL SIGNED BY THE ENGINEER AND ACCEPTED BY THE APPROVING AGENCY. THESE PLANS ARE NOT TO BE REPRODUCED IN WHOLE OR IN PART WITHOUT THE PERMISSION OF GRIT ENGINEERING INC.
- CHANGES TO DRAWINGS ARE NOT PERMITTED UNTIL REVIEWED AND APPROVED BY THE ENGINEER AND ACCEPTED BY THE APPROVING AUTHORITY.
- CONTRACTOR TO VERIFY THAT THE DRAWINGS BEING USED FOR THE CONSTRUCTION ARE THE MOST RECENT VERSION.
- UTILITY LOCATES AND ALL APPLICABLE PERMITS ARE TO BE OBTAINED PRIOR TO THE START OF CONSTRUCTION AND INSPECTION BEING COMPLETED.
- THE CONTRACTOR IS TO VERIFY THE EXISTING CONDITION OF THE SITE. THE VERIFICATION INCLUDES AND NOT LIMITED TO THE SERVICE LOCATION, SERVICE ELEVATIONS, UTILITY CONFLICTS AND BENCHMARK ELEVATIONS. ANY DISCREPANCIES ARE TO BE REPORTED TO THE ENGINEER IMMEDIATELY AND PRIOR TO THE CONTINUATION OF CONSTRUCTION.
- LEGAL INFORMATION AND EXISTING TOPOGRAPHIC INFORMATION TAKEN FROM PLAN PREPARED BY NA GEOMATICS, RECEIVED NOVEMBER 9, 2021.
- THE CONTRACTOR IS TO OBTAIN CONSENT FROM THE NEIGHBOR IN THE FORM OF WRITTEN CORRESPONDENCE GRANTING PERMISSION TO ENTERING THE PROPERTY TO COMPLETE ANY CONSTRUCTION ACTIVITY. THE WRITTEN CONSENT IS TO BE PROVIDED TO THE APPROVING AUTHORITY PRIOR TO THE CONTINUATION OF WORK FOR APPROVAL. THE CONTRACTOR WILL ASSUME LIABILITY FOR ALL WORKS IF FAILURE TO COMPLY.
- THIS DRAWING IS TO BE READ COMBINATION WITH THE FOLLOWING:
 - STORMWATER MANAGEMENT REPORT, DECEMBER 20TH, 2021.
- DURING THE CONSTRUCTION, THE CONTRACTOR ASSUMES ALL LIABILITY FOR DAMAGE TO ALL EXISTING FEATURES AND STRUCTURES. THE CONTRACTOR WILL BE RESPONSIBLE FOR ALL RESTORATION AND RESTORED TO EXISTING CONDITION OR BETTER.
- THESE PLANS ARE TO BE USED FOR SERVING AND GRADING ONLY. ANY OTHER INFORMATION SHOWN IS FOR ILLUSTRATION PURPOSES ONLY. THESE PLANS MUST NOT BE USED TO SITE THE PROPOSED BUILDING.
- THE CONTRACTOR SHALL ASSUME ALL LIABILITY FOR ANY DAMAGE TO EXISTING WORKS. THE CONTRACTOR IS RESPONSIBLE FOR RESTORATION OF ALL DAMAGED AND/OR DISTURBED PROPERTY WITHIN THE MUNICIPAL RIGHT-OF-WAY TO THE APPROVING AGENCY STANDARDS.
- ALL UNDERGROUND SERVICES ARE TO BE CONSTRUCTED IN FULL COMPLIANCE WITH THE ONTARIO PROVINCIAL BUILDING CODE (PART 7, PLUMBING), THE ONTARIO PROVINCIAL STANDARD SPECIFICATIONS (OPSS) AND THE REQUIREMENTS OF THE TOWN OF ST. MARYS, WHICH CODES AND REGULATIONS SHALL SUPERSEDE ALL OTHERS.
- SITE SERVICING CONTRACTOR TO TERMINATE ALL SERVICES 1 METRE FROM FOUNDATION WALL.
- FILTER FABRIC TO BE TERRAFIX 270R OR APPROVED EQUAL.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL TRAFFIC AND SAFETY MEASURES DURING THE CONSTRUCTION PERIOD INCLUDING THE SUPPLY, INSTALLATION AND REMOVAL OF ALL NECESSARY SIGNALS, DELINEATORS, MARKERS, AND BARRIERS. ALL SIGNS, ETC. SHALL CONFORM TO THE STANDARDS OF THE TOWN OF ST. MARYS AND THE MTO MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES.
- THE POSITION OF POLE LINES, CONDUITS, WATERMAINS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, THE CONTRACTOR SHALL INFORM HIMSELF OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.
- FOLLOWING COMPLETION OF PROPOSED WORKS AND PRIOR TO OCCUPANCY INSPECTION, ALL STORM SEWERS ARE TO BE FLUSHED, AND ALL CATCHBASIN AND CATCHBASIN MANHOLE SUMPS ARE TO BE CLEANED OF DEBRIS AND SILT.














2. INSPECTION AND CERTIFICATION

- GRIT ENGINEERING INC. REQUIRES A MINIMUM OF 24 HOURS NOTICE PRIOR TO THE REQUIRED INSPECTION BE REQUESTED. INSPECTIONS ARE REQUIRED TO VERIFY PIPE INSTALLATION (MATERIALS, SIZE, LOCATION AND ELEVATION), STRUCTURE PLACEMENT, SURFACE MATERIAL AND FINISHED GRADING.
 - CONSTRUCTION WORKS WITHIN THE PUBLIC RIGHT-OF-WAY REQUIRE FULL TIME INSPECTION.
 - CONSTRUCTION WORKS WITHIN PRIVATE LANDS ARE REQUIRED ON A PART TIME AND AS NEEDED BASIS.
- FAILURE TO COMPLY WITH GRIT ENGINEERING INC. INSPECTION REQUIREMENTS, WILL RESULT IN ADDITIONAL CONSTRUCTION INSPECTION AND VERIFICATION AT THE EXPENSE OF THE CONTRACTOR.
- STORM SEWERS AND SERVICING**
 - PIPE BEDDING FOR RIGID PIPE TO BE CLASS 'B' AS PER OPSD 802.030, 802.031, OR 802.032. PIPE BEDDING FOR FLEXIBLE PIPE TO BE AS PER OPSD 802.010. BEDDING MATERIAL AND COVER MATERIAL TO BE GRANULAR 'A'. TRENCH BACKFILL TO BE NATIVE MATERIAL REPLACED IN 300mm LIFTS AND COMPACTED TO 95% STANDARD PROCTOR MAXIMUM DRY DENSITY.
 - STORM SEWERS 200mmØ TO 450mmØ SHALL BE POLYVINYL CHLORIDE (PVC) PIPE DR35 ASTM-D3034 OR RIBBED PVC SEWER PIPE CSA B182.4-M90 ASTM-F794 WITH INTEGRAL BELL AND SPIGOT UTILIZING FLEXIBLE ELASTOMERIC SEALS. RIBBED PVC NOT TO BE USED WITH RIGHT-OF-WAY.
 - MAINTENANCE HOLES AND MAINTENANCE HOLE CATCHBASINS TO BE 1200mmØ PRECAST WITH ALUMINIUM STEPS AT 300mm CENTRES AS PER OPSD 701.010 UNLESS OTHERWISE SPECIFIED.

- MAINTENANCE HOLES TO BE BENCHMARK PER OPSD 701.021.
- CATCHBASIN STRUCTURES 600mmx600mm PER OPSD 705.010
- DITCHINLET CATCHBASIN STRUCTURES 600mmx1200mm PER OPSD 705.040 (TYPE B)
- DOUBLE CATCHBASIN STRUCTURES 600mmx1450mm PER OPSD 705.020
- OIL GRIT SEPARATOR TO BE ADS MODEL FD-4HC OR APPROVED EQUIVALENT
- RAINFALL DATA: STRATFORD CATCHMENT AREA: ±1.38 Ha CATCHMENT IMPERVIOUS PERCENTAGE: 80.0% QUALITY LEVEL: ENHANCED FLOW RATE: ± 90 L/s
- CATCHBASIN MAINTENANCE HOLES, CATCHBASINS AND DITCH INLET CATCHBASINS TO HAVE A MINIMUM 600mm DEEP SUMP.
- MAINTENANCE HOLE AND CATCHBASIN, FRAMES, GRATES, CASTINGS AND LIDS TO BE QUALITY GREY IRON ASTM A8 CLASS 30B.
- STORM MAINTENANCE HOLE LIDS TO BE PER OPSD 401.010 - TYPE 'B' CATCHBASIN AND CATCHBASIN MAINTENANCE HOLE GRATES TO BE PER OPSD 400.100.
- STORM SEWERS AND SERVICES TO HAVE MINIMUM 1.2m COVER TO TOP OF PIPE. WHERE COVER TO TOP OF PIPE IS DEFICIENT, CONTRACTOR SHALL INSTALL SHALLOW BURIED SEWER PIPE PER DETAIL THIS SHEET OR OTHER ENGINEER-APPROVED EQUIVALENT.

- FIRE WATER SUPPLY SERVICE**
 - DRY HYDRANTS TO BE INSTALLED IN ACCORDANCE TO NFPA 1142.
 - FIRE MAIN IS TO BE 200mmØ GALVANIZED STEEL SCHEDULE 80 OR APPROVED EQUIVALENT.
 - FIRE MAIN PIPE BEDDING TO BE CLASS 'B' AS PER OPSD 802.030. PIPE BEDDING AND COVER MATERIAL TO BE GRANULAR 'A' OR APPROVED EQUIVALENT. TRENCH BACKFILL TO BE APPROVED NATIVE MATERIAL AND PLACED IN 300mm THICK LIFTS COMPACTED TO A MINIMUM OF 95% STANDARD PROCTOR MAXIMUM DRY DENSITY.
- EROSION AND SEDIMENT CONTROL**
 - PRIOR TO THE START OF ANY CONSTRUCTION THE CONTRACTOR IS TO INSTALL THE EROSION AND SEDIMENT CONTROLS IN ACCORDANCE TO THE APPROVED PLAN.
 - NO ALTERNATE EROSION AND SEDIMENT CONTROLS ARE PERMITTED WITHOUT APPROVAL FROM THE ENGINEER AND APPROVING AUTHORITY.
 - ADDITIONAL EROSION AND SEDIMENT CONTROLS MAY BE REQUIRED AS THE CONSTRUCTION PROGRESSES. THE CONTRACTOR TO INSTALL ADDITIONAL MEASURES AS REQUIRED BY THE ENGINEER AND APPROVING AUTHORITY.
 - THE CONTRACTOR IS TO PERFORM REGULAR MAINTENANCE, REPAIRS AND REPLACEMENT ON ALL CONTROLS TO ENSURE PROPER FUNCTIONING UNTIL PROJECT IS COMPLETE.
 - EROSION CONTROL FENCING TO BE INSTALLED AROUND BASE OF ALL STOCKPILES. ALL STOCKPILES TO BE KEPT 2.5m MINIMUM FROM PROPERTY LINE.
 - EROSION PROTECTION TO BE PROVIDED AROUND ALL STORM AND SANITARY MHS AND CBS.
 - ADDITIONAL EROSION CONTROL MEASURES MAY BE REQUIRED AS SITE DEVELOPMENT PROGRESSES. CONTRACTOR TO PROVIDE ALL ADDITIONAL EROSION CONTROL STRUCTURES.
 - CONTRACTOR TO CLEAN ROADWAY AND SIDEWALKS OF SEDIMENTS RESULTING FROM CONSTRUCTION TRAFFIC FROM THE SITE EACH DAY.
 - THE CONTRACTOR IS TO REMOVE ALL EROSION AND SEDIMENT CONTROLS UNTIL DEVELOPMENT IS COMPLETE AND VEGETATION PROPOSED FINISHED HARD SURFACE MATERIALS ARE INSTALLED AND VEGETATION IS STABILIZED WITH MATURE GROWTH.

- MAINTENANCE RECOMMENDATIONS**
 - EROSION CONTROL STRUCTURES TO BE MONITORED REGULARLY AND ANY DAMAGE REPAIRED IMMEDIATELY. SEDIMENTS TO BE REMOVED WHEN ACCUMULATIONS REACH A MAXIMUM OF 1/3 THE HEIGHT OF THE FENCE.
 - OWNERS REPRESENTATIVE TO MONITOR EROSION CONTROL STRUCTURES TO ENSURE FENCING IS INSTALLED AND MAINTENANCE IS PERFORMED TO MUNICIPALITY REQUIREMENTS.



CONTRACTOR NOTES:

CONTRACTORS MUST CHECK AND VERIFY ALL DIMENSIONS AND REPORT ANY ERRORS TO THE ENGINEER PRIOR TO COMMENCEMENT OF WORK.

ALL DRAWINGS SHALL REMAIN THE PROPERTY OF THE ENGINEER AND SHALL NOT BE REUSED WITHOUT THE ENGINEER'S WRITTEN PERMISSION.

DRAWING SHOULD NOT BE SCALED FOR DIMENSIONS PURPOSES.

BENCHMARK
ELEVATIONS ARE RELATED TO TOP SPINDLE OF FIRE HYDRANT ON THE NORTH SIDE OF QUEEN STREET AT THE CORNER OF QUEEN AND 120 ROAD.

ELEVATION: 235.88m

No.	ISSUED DESCRIPTION	DATE
1	ISSUED FOR CLIENT REVIEW	2021-11-12
2	ISSUED FOR SITE PLAN APPROVAL	2021-11-16
3	REVISED PER MUNICIPAL COMMENTS	2021-12-20
4		
5		



ROAD 120 SELF STORAGE UNITS

PROJECT INFORMATION: 60 ROAD 120, ST. MARYS, ONTARIO

C & C MANAGEMENT

CLIENT INFORMATION:

NOTES AND DETAILS

DRAWING NAME:

PROJECT No: **GE021-21**

SCALE: **AS SHOWN**

DRAWING No: **C500**

SHEET SET No: **4 of 4**